

Building Specification Sheet For Armourcoat Spatulata Finish BSS6

Product:	ARMOURCOAT Polished Plaster
Manufacturer:	Armourcoat Ltd. Morewood Close, London Road, Sevenoaks, Kent. TN13 2HU Web: www.armourcoat.com
Location:	(e.g. Walls and ceilings to reception area and lift lobby)
Drawings:	Refer to drawings no.
Background:	Substrate to be prepared in accordance with Armourcoat Ltd's guidance: <ul style="list-style-type: none">• Plasterboard/Drylining Installation and Finishing (SSS1)• Plasterboard/Drylining with Armourcoat AntiCrack Skimcoat (SSS2)• Brick, Block and Concrete (SSS3)• Glasroc and GRG (SSS4)• Previously Decorated (SSS5)• Sand / Cement Render (SSS6)• MDF (SSS7)• Bluclad Board (SSS9)• Exterior Application (SSS10)
Preparation:	Ensure a true, flat and even surface with wall surfaces that are constructed in accordance with specialist's requirements. For surfaces not uniformly flat and/or smooth mix and apply Armourcoat Keycoat K149 in accordance to manufacturer's working instructions. Substrates must be free of curing compounds, dust, and other impurities such as oil, grease and salts.
Primer:	For surfaces with uneven suction apply Armourcoat K40 Primer in accordance with manufacturers recommendations.
Finish:	Apply 4, 5 or 6 thin coats of Armourcoat pre-mixed plaster (Spatulata P80) in successively thinner layers applied over one or two days. Exact number of coats to specialist's requirements and determined by the level of sheen required. Leave overnight or until completely dry.
Thickness:	approx. 0.5 mm – 1.0 mm
Colour:	Armourcoat ref: e.g. SO S0033
Waxing:	As required. Leave to dry overnight before waxing. Supply and apply Armourcoat wax polish (Ref. White Wax) sparingly in accordance with manufacturer's working instructions. Refer to Clause 250 in General Requirements. Apply and polish to achieve the specified finish.
Guarantee:	10 year guarantee covering materials and application for internal use.
Application:	The system is to be supplied and applied by an Armourcoat Ltd or an Accredited Applicator Agent in accordance with Armourcoat's recommendations and specifications. Refer to attached specification sheets for details of installation.

Whilst every attempt has been made to ensure the accuracy and reliability of the information contained in this document, the information should not be relied upon as a substitute for formal advice. Armourcoat Ltd, its employees and agents will not be liable for any loss or damage, of any kind, arising out of or in connection with the use of this document. Please refer to the company disclaimer for further details.

SPD BSS6 0504 ©

Armourcoat Limited
Morewood Close London Road
Sevenoaks Kent TN13 2HU United Kingdom
Tel: +44 (0)1732 460 668 Fax +44 (0)1732 450 930
Email: technical@armourcoat.co.uk

web: www.armourcoat.com